



W264 S8470 Oakdale Dr, Mukwonago, WI 53149 - P: +1 262-261-6100 - F: 262-378-3001 - www.frostpoint.net

NXT APL-LT

Low-Temperature Synthetic Ammonia Liquid Transfer Pump Lubricant

NXT APL-LT is formulated specifically for ammonia liquid transfer pumps. NXT APL-LT is for use in extremely low-temperature applications. NXT APL-LT has superior rust and corrosion additives to protect system parts.

ATTRIBUTES

- Maintains fluidity in low temperatures to protect seals
- High viscosity index for superior pumpability at lower temperatures and better protection at high temperatures
- Thermal and oxidative stability promote longer fluid life and extended oil-drain intervals
- Protects against rust, corrosion, carbon and varnish
- Excellent film strength and anti-wear properties for better protection of compressor parts
- High flash and auto-ignition points for added safety

TYPICAL LUBRICANT PROPERTIES

NXT APL-LT Grades	15
Viscosity Index	119
Viscosity cSt @ 40°C	14.2
Viscosity cSt @ 100°C	3.5
Flash Point °F (°C)	350 (176)
Pour Point °F (°C)	-70 (-57)
Copper Corrosion, 24 Hr	1a
Demulsibility, 130°F, 30 Min	40/40/0
Color	<.5